



- STANDARD SWITCH FEATURES:
- 4 POLE KNIFE TYPE - NON FUSIBLE
 - 1000 VOLT INSULATION CLASS
 - NON FUSIBLE
 - NON LOAD-BREAK
 - NEMA 12 ENCLOSURE
 - EXTERNAL PADLOCKABLE HANDLE OPERATOR
 - TOP ENTRY, BOTTOM EXIT
 - ANSI 61 GRAY FINISH

AVAILABLE OPTIONS:

DESCRIPTION OF OPTIONS	SUFFIX
AUXILIARY SWITCHES QTY 2; TWO AUXILIARY SWITCHES FORM "C", (D) CLOSED AND (E) OPEN (NOT WIRED)	1X
AUXILIARY SWITCHES QTY 4; FOUR AUXILIARY SWITCHES FORM "C", (E) CLOSED AND (D) OPEN (NOT WIRED)	2X
TERMINAL BOARD	TB
AUXILIARY SWITCHES WIRED TO A TERMINAL BOARD	K1
KEY INTERLOCK PROVISION IN THE OPEN POSITION	K2
KEY INTERLOCK PROVISION IN THE CLOSED POSITION	K3
KEY INTERLOCK PROVISION IN THE OPEN AND CLOSED POSITION	ORDER BY DESCRIPTION
KEY INTERLOCK PROVIDED BY FILMOR - SINGLE KEY	V
POLYCARBONATE WINDOW IN DOOR	SR
NEMA 3R ENCLOSURE	A
NEMA 4 ENCLOSURE	4
NEMA 4X ENCLOSURE	4X

TERMINAL DIMENSIONS

AMP	MODEL	A	B	C
200	EKM0210-4P	5.69	2.85	4.09
400	EKM0410-4P	5.81	2.91	4.94
600	EKM0610-4P	6.06	3.03	5.53

Filmor Inc.
 P.O. BOX 5200
 ALLIANCE, OHIO 44001
 DISCONNECT SWITCH LAYOUT
 200 THRU 600 AMP
 DATE: 10/22/07
 DRAWN BY: JRM
 CHECKED BY: J.S.
 SCALE: NONE
 PART NO: 01227344